



PRODUCT PERFORMANCE PASSION

|                           |                       |
|---------------------------|-----------------------|
| Article                   | <b>NEW ZERMATT WR</b> |
| Category                  | <b>S3 WR SRC</b>      |
| Sizes                     | <b>36 - 48</b>        |
| Width                     | <b>11</b>             |
| Weight (half pair, sz 42) | <b>690 gr</b>         |
| Metal free                | <b>Yes</b>            |
| Certification             | <b>CE</b>             |

|                                 |                                                                                                                                                                                                                                    |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>UPPER</b>                    | full grain leather, high visibility rear insert                                                                                                                                                                                    |
| <b>WATERPROOF</b>               | <b>PERF-DRY120</b> membrane, totally waterproof and brethable                                                                                                                                                                      |
| <b>LINING</b>                   | extremely breathable polyamide lining. It absorbs moisture quickly and ensures a greater comfort during the whole working day. Optimal resistance to abrasion and anti-bacterial                                                   |
| <b>TOE CAP</b>                  | non-magnetic toecap, from composite materials. 50% lighter then steel                                                                                                                                                              |
| <b>ANTI-PERFORATION MIDSOLE</b> | non-magnetic, perforation resistance composite fabric plate. It is 40% lighter and more flexible than steel plate and at the same time guarantees an optimal protection covering 100% of the foot surface. Certified EN 12568:2010 |
| <b>FOOTBED</b>                  | insole PU 10mm expanded, covered with antibacterial fabric                                                                                                                                                                         |
| <b>SOLE</b>                     | PU double density with optimal absorption of strains on the vertebral column thanks to the use of expanded PU midsole. Maximum stability                                                                                           |



**WATERPROOF**



**PERF-DRY120**



**E·LITE S**  
**Rain & Cold**

|                                                    | Requirements             | Test Results |
|----------------------------------------------------|--------------------------|--------------|
| <b>UPPER</b>                                       | <b>EN ISO 20345:2011</b> |              |
| Water Vapour Permeability                          | mg/cmq*h ≥ 0,8           | 5,7          |
| Water Vapour Coefficient                           | mg/cmq ≥ 15              | 53,3         |
| <b>LINING</b>                                      |                          |              |
| Water Vapour Permeability                          | mg/cmq*h ≥ 2             | 11,1         |
| Water Vapour Coefficient                           | mg/cmq ≥ 20              | 97,7         |
| <b>TOECAP</b>                                      |                          |              |
| Impact resistance: clearance under the toecap      | mm ≥ 14                  | 14           |
| Compression resistance: clearance under the toecap | mm ≥ 14                  | 14           |
| <b>ANTI-PERFORATION MIDSOLE</b>                    |                          |              |
| Penetration resistance (EN ISO 12568:2010)         | N ≥ 1100                 | ≥ 1100       |
| <b>ELECTRICAL RESISTANCE</b>                       |                          |              |
| - wet condition (85% relative humidity)            | MΩ ≥ 0,1                 | 300          |
| - dry condition (30% relative humidity)            | MΩ ≤ 1000                | 650          |
| <b>SOLE</b>                                        |                          |              |
| Abrasion resistance: relative volume loss          | mm <sup>3</sup> ≤ 150    | 45           |
| Flexing resistance: cut growth                     | mm ≤ 4                   | 1,5          |
| Resistance to fuel oil: volume increase            | % ≤ 12                   | 1,1          |
| Energy absorption of seat region                   | J ≥ 20                   | 23           |
| Slip resistance on steel ground with glycerine     | 7° Heel ≥ 0,13           | 0,15         |
|                                                    | Flat ≥ 0,18              | 0,19         |
| Slip resistance on ceramics ground with detergent  | 7° Heel ≥ 0,28           | 0,33         |
|                                                    | Flat ≥ 0,32              | 0,46         |

Per-Halla Srl. All rights reserved. The data indicated in this sheet can be modified without notice following evolution in materials and products.  
Version 1.0

